



AFT-A ALUMINUM FOIL TAPE

COMPOSITION

Aluminum Foil with Synthetic Acrylic Adhesive.

PRODUCT APPLICATIONS

- Ducts, Fiberglass systems, Seams, Joints, Vapor Barriers, FSK Systems.

STORAGE AND HANDLING

The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 50 Yards / 45.72 Meters for **2.8 Mil** through **3.6 Mil**
- 60 Yards / 54.86 Meters for **5.0** and **7.0 Mil** Models
- Contact Tape Providers for other available sizes



•**Note:** Contact Tape Providers for Custom Printed Cores

PHYSICAL PROPERTIES

Thickness	Product code	Tensile Strength	Adhesion	Elongation
2.8 Mil	AFT-12A	50 YDS	73 oz/in	10.3 lbs/in
3.2 Mil	AFT-16A	50 YDS	73 oz/in	12.6 lbs/in
3.6 Mil	AFT-20A	50 YDS	73 oz/in	17.1 lbs/in
5.0 Mil	AFT-30A	50 YDS	73 oz/in	17.1 lbs/in
7.0 Mil	AFT-50A	50 YDS	73 oz/in	18.1 lbs/in

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
1/2	12
3/4	18
1	24
1.5	36
2	48
2.5	63
3	72
4	96
6	144
12	300
Custom Available	