



AFT-A ALUMINUM FOIL TAPE

COMPOSITION

Aluminum Foil with Synthetic Acrylic Adhesive.

PRODUCT APPLICATIONS

- Ducts, Fiberglass systems, Seams, Joints, Vapor Barriers, FSK Systems.

STORAGE AND HANDLING

The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 50 Yards / 45.72 Meters for **2.8 Mil** through **3.6 Mil**
- 60 Yards / 54.86 Meters for **5.0 Mil** through **7.0 Mil** Models
- Contact Tape Providers for other available sizes.

TABLE OF MEASUREMENTS STANDARD WIDTH(S)

IN	MM
1/2	12
3/4	18
1	24
1.5	36
2	48
2.5	63
3	72
4	96
6	144
12	300
Custom Available	



PHYSICAL PROPERTIES

Product code	AFT12A	AFT16A	AFT20A	AFT30A	AFT50A
Thickness	2.8 Mil	3.2 Mil	3.6 Mil	5.0 Mil	7.0 Mil
Tensile Strength	10.3 lbs/in	12.6 lbs/in	17.1 lbs/in		
Peel Adhesion	73 oz/in	73 oz/in	73 oz/in	73 oz/in	73 oz/in
Elongation	3%	3%	3.5%	5%	
Temperature Resistance	248°F	248°F	248°F	302°F	300°F
Yards	50 Yards	50 Yards	50 Yards	60 Yards	60 Yards

•Note: Contact Tape Providers for Custom Cores