

AFTSW ALUMINUM FOIL TAPE NO LINER



COMPOSITION

Malleable aluminum foil coated with an acrylic adhesive.

PRODUCT APPLICATIONS

- HVAC, construction, and industrial use.

STORAGE AND HANDLING

The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 60 Yards / 54.86 Meters for **3.6 Mil** and **4.8 Mil** Models
- Contact Tape Providers for other available sizes



• Note: Contact Tape Providers for Custom Printed Cores

PHYSICAL PROPERTIES

| Thickness | Product code | Tensile Strength | Adhesion | Elongation |
|-----------|--------------|------------------|----------|------------|
| 3.6 Mil | AFT20SW | 60 YARDS | 40 oz/in | 26 lbs/in |
| 4.8 Mil | AFT30SW | 60 YARDS | 40 oz/in | 36 lbs/in |

TABLE OF MEASUREMENTS

STANDARD WIDTH(S):

3.6 MIL

| IN | MM |
|------------------|----|
| 1/2 | 12 |
| 3/4 | 18 |
| 1 | 24 |
| 1.5 | 36 |
| 2 | 48 |
| Custom Available | |

4.8 MIL

| IN | MM |
|------------------|----|
| 1/2 | 12 |
| 3/4 | 18 |
| 1 | 24 |
| 1.5 | 36 |
| 2 | 48 |
| 3 | 72 |
| 4 | 96 |
| Custom Available | |