



AST32 ANTI SLIP TAPE

COMPOSITION

Aggressive acrylic adhesive. 60 grit silicon carbide.

PRODUCT APPLICATIONS

- Indoor And Outdoor. Walkways, Ramps, Stairways, Machine Shops, Work Areas, High Traffic Areas.

PHYSICAL PROPERTIES

STANDARD METRIC

Tensile Strength	13 lbs/in	57.84 N/25 mm
Adhesion to Steel	54 oz/in	15.01 N/25 mm
Thickness	32 mils	0.81 mm
Elongation	25%	25%
Temperature Resistance	175 F	80°C

STORAGE AND HANDLING

Storage Conditions: From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

Note: The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 60 Feet 20 Yards
- Contact Tape Providers for other available sizes

COLOR (S)

Black, Black and Yellow, Clear, Dark Blue, Dark Green, Gray, Racing Orange, Red, White, Yellow, Fluorescent Orange, Fluorescent Red, and Fluorescent Yellow.

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
1	25
1.5	38
2	50
3	75
4	100
6	150
12	300
Custom Available	



- Note:** Contact Tape Providers for Custom Printed Cores