

DCFAUHBE

DOUBLE-SIDED

FOAM TAPE - HIGH BOND



**TEMPERATURE
RESISTANT**



**AUTOMOTIVE
INDUSTRY**



**STRONG
BOND**

DESCRIPTION

Gray foamed acrylic system for extremely strong bonding in demanding structural applications.

FEATURES

- Ultra-high bond acrylic adhesive
- High shear strength & adhesion
- Excellent resistance to UV, chemicals, and solvents
- Conformability for indoor/outdoor surfaces

ALTERNATIVES

Alternative to 3M #4941, #4941F, #4947F, #4949, #4611, #5344, #5605, #5952; ADCO #1140; Hi-Bond #6110G; ORAFOL ORABONDTM #UHB03110G, #3600.

STORAGE CONDITIONS

Cool and dry area. No direct sun.

TECHNICAL SPECS

Thickness & Model	Adhesion	Tensile Strength	Shear Strength	Temp Resist	Length
16 Mil (DCFAUHB16E)	118 oz/in	107 lb/in	100 psi (24h)	356°F	72 yds
25 Mil (DCFAUHB25E)	120 oz/in	108 lb/in	102 psi (24h)	356°F	36 yds
31 Mil (DCFAUHB31E)	132.8 oz/in	92 lb/in	92 psi (24h)	356°F	36 yds
45 Mil (DCFAUHB45E)	139 oz/in	85 lb/in	85 psi (24h)	356°F	36 yds
60 Mil (DCFAUHB60E)	139.2 oz/in	78 lb/in	78 psi (24h)	392°F	27.34 yds
80 Mil (DCFAUHB80E)	139.2 oz/in	71 lb/in	75 psi (24h)	356°F	18 yds

SIZES

IN	MM
1/4	6.3
3/8	9.5
1/2	12.7
3/4	19
1	25.4
3/7	94.0



CUSTOM SIZES

At Tape Providers we understand that each project is different. We can manufacture the size according to your requirement.



8465 W 44th Ave
Suite 128
Hialeah, Florida 33018



+1 786 565 9858
www.tapeproviders.com