Product Technical Data Sheet

This page covers product technical specifications along with product properties and usage.

DCPT43R

DOUBLE SIDED CREPE LINER TAPE

COMPOSITION

Crepe paper coated on both sides with an aggressive natural rubber/resin adhesive. White crepe paper release liner.

PRODUCT APPLICATIONS

-Used in the printing industry, textile manufacturing (twisting/spinning process), steel rule die-makers/die-cutters (make-ready), & carpet installation. For bonding, mounting, holding, joining, core start-ups, and splicing applications.

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	23 lbs/in	40.74 n/cm
Adhesive Thickness	6.0 mil	0.152 mm
Backing Thickness	10.4 mil	0.264 mm
Adhesion to Steel	47 oz/in	5.22 n/cm
Elongation	8.5%	8.5%
Quick Stick	20 oz/in	2.22 n/cm

STORAGE AND HANDLING

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

STANDARD LENGTH (S)

- 36 yards
- 33 meters
- Contact Tape Providers for other available sizes

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
1/4	6
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
6	144
12	300
48	1219
Custom Available	

- **Note:** Contact Tape Providers for Custom Cores