



DCPT70R DOUBLE SIDED PAPER TAPE

COMPOSITION

Flatback paper coated on both sides with a high shear/aggressive solvent based natural rubber resin adhesive

PRODUCT APPLICATIONS

- Golf Club Grips, Club Repair & Maintenance, and Wrapping other Sports Equipment.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	34 lbs/in	60.23 n/cm
Adhesive Thickness	7.0 mil	0.178 mm
Backing Thickness	12 mil	0.305
Adhesion to Steel	52 oz/in	5.78 n/cm
Elongation	3%	3%
Unwind	11 oz/in	1.22 n/cm

Meets spec CID A-A-180C, Type II (replaces UU-T-91E).

STORAGE AND HANDLING

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.


STANDARD LENGTH (S)

- 36 yards
- 33 meters
- Contact Tape Providers for other available sizes

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
1/4	6
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
6	144
12	300
48	1219
Custom Available	



• **Note:** Contact Tape Providers for Custom Printed Cores