



## DCPVC55 DOUBLE SIDED PVC TAPE

### COMPOSITION

White PVC film coated on both sides with a solvent based acrylic adhesive

### PRODUCT APPLICATIONS

Used extensively for mounting signs and large format graphics. For bonding trims in automotive and other industries; securing attachment of extruded plastic profiles in furniture industries.

### PHYSICAL PROPERTIES

### STANnoDARD METRIC

Adhesion to Steel	80 oz/in	22.24 N/25 mm
PVC Film Thickness	1.5 mil	0.038 mm
Exclusive Liner Thickness	5.5 mil	0.140 mm
Temperature Resistance	-40 to 158 F	-4.44 to 70°C

### STORAGE AND HANDLING

**Storage Conditions:** From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

**Note:** The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

### STANDARD LENGTH (S)

- 35 Yards 33 Meters
- Contact Tape Providers for other available sizes

### COLOR (S)



White

### TABLE OF MEASUREMENTS

#### STANDARD WIDTH(S)

IN	MM
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
Custom Available	



- **Note:** Contact Tape Providers for Custom Printed Cores