



DCPVC78

DOUBLE SIDED PVC TAPE

COMPOSITION

PVC film coated on both sides with a modified acrylic adhesive, solvent free, based on aqueous dispersions.

PRODUCT APPLICATIONS

Ideal for rough & LSE surfaces

PHYSICAL PROPERTIES

STANDARD METRIC

Adhesion to Steel	157 oz/in	43.65 N/25 mm
Shear Resistance	14 lbs/in ²	14 lbs/in ²
PVC Film Thickness	3.2 mil	0.081 mm
Adhesive Thickness	2.3 mil	0.058 mm
Total Thickness	7.87 mil	0.200 mm
Temperature Resistance	-40 to 176 F	-4.44 to 80°C

STORAGE AND HANDLING

Storage Conditions: From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

Note: The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 35 Yards 33 Meters
- 60 Yards 55 Meters
- Contact Tape Providers for other available sizes

COLOR (S)



Clear



Black

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
Custom Available	



- **Note:** Contact Tape Providers for Custom Cores