



DCPVC98

DOUBLE SIDED PVC TAPE

COMPOSITION

White PVC film coated on both sides with an aggressive, solvent-free, modified acrylic adhesive.

PRODUCT APPLICATIONS

Exhibits good tack and adheres extremely well to rough surfaces, such as chipboards, and LSE substrates.

PHYSICAL PROPERTIES

STANDARD

METRIC

Adhesion to Steel	168 oz/in	46.70 N/25 mm
PVC Film Thickness	3.2 mil	0.081 mm
Exclusive Liner Thickness	9.84 mil	0.250 mm
Tack	62 oz/in	17.24 N/25mm
Temperature Resistance	-40 to 266 F	-4.44 to 130°C

STORAGE AND HANDLING

Storage Conditions: From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

Note: The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 36 Yards 33 Meters
- Contact Tape Providers for other available sizes

COLOR (S)



White

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
Custom Available	



- **Note:** Contact Tape Providers for Custom Cores