



## ETB7xx Electrical Tape General Grade

### COMPOSITION

Plasticized PVC with rubber-based adhesive.

### PRODUCT APPLICATIONS

- Wire and Cable Insulation, Bundling, and Splicing.

### PHYSICAL PROPERTIES

#### STANDARD METRIC

Tensile Strength	16 lbs/in	71.18 N/25 mm
Adhesion to Steel	14 oz/in	3.89 N/25 mm
Thickness	7 mils	0.18 mm
Elongation	200%	200%
Temperature Resistance	176 F	80°C

### STORAGE AND HANDLING

**Storage Conditions:** From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

**Note:** The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

### STANDARD LENGTH (S)

- 30 Feet 10 Yards
- 60 Feet 20 Yards
- 66 Feet 2 Yards
- 108 Feet 36 Yards
- Contact Tape Providers for other available sizes

### COLOR (S)

**Black**

### TABLE OF MEASUREMENTS

#### STANDARD WIDTH(S)

IN	MM
0.50	12
0.75	19
1	24
1.5	36
2	48
3	72
4	96
Custom Available	



- **Note:** Contact Tape Providers for Custom Printed Cores