



## FTC14

### Electrical Tape General Grade

#### COMPOSITION

Plasticized PVC with rubber-based adhesive.

#### PRODUCT APPLICATIONS

- Wire and Cable Insulation, Bundling, and Splicing.

#### PHYSICAL PROPERTIES

#### STANDARD

#### METRIC

|                        |           |              |
|------------------------|-----------|--------------|
| Tensile Strength       | 46 lbs/in | 204 N/25 mm  |
| Adhesion to Steel      | 14 oz/in  | 3.89 N/25 mm |
| Thickness              | 13 mils   | 0.18 mm      |
| Elongation             | 10%       | 10%          |
| Temperature Resistance | 176 F     | 80°C         |

#### STORAGE AND HANDLING

**Storage Conditions:** From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

**Note:** The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

#### STANDARD LENGTH (S)

- 60 Yards / 54.86 meters
- Contact Tape Providers for other available sizes

#### COLOR (S)

**Black**

#### TABLE OF MEASUREMENTS

##### STANDARD WIDTH(S)

| IN               | MM |
|------------------|----|
| 0.75             | 19 |
| 1.5              | 36 |
| 2                | 48 |
| Custom Available |    |



- **Note:** Contact Tape Providers for Custom Cores