



GTC12 GAFFER TAPE LOW GLOSS FINISH

COMPOSITION

Polyethylene-coated cloth laminated to a low gloss finish film, coated with a Natural rubber-based adhesive.

PRODUCT APPLICATIONS

- Film and TV Shoots, Studio filming, Theatre/Stage Production, Automotive industry, Sports Productions, Churches, Film Schools, Broadcasting Classes, Box-Sealing, Lighting, Audio/Visual Technicians.

PHYSICAL PROPERTIES

STANDARD METRIC

Tensile Strength	36 lbs/in	160.17 N/25 mm
Adhesion to Steel	29 oz/in	8.06 N/25 mm
Thickness	11.8 mils	0.299 mm
Elongation	12%	12%
Temperature Resistance	176 F	80°C

STORAGE AND HANDLING

Storage Conditions: From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

Note: The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 60 Feet 20 Yards
- 135 Feet 45 Yards (Upon Request)
- Contact Tape Providers for other available sizes

COLOR (S)

Black, White, Gray, Red, Yellow, Dark Blue, Light Blue, Dark Green, Olive Drab, Brown, and Burgundy.

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
6	144
12	288
Custom Available	



- Note:** Contact Tape Providers for Custom Cores