

## SPTA UHMW TAPE

### COMPOSITION

Ultra High Molecular Weight Polyethylene with Acrylic Adhesive.

### PRODUCT APPLICATIONS

- Reduce Friction, Noise, Wire Harnessing. For Conveyors, Chutes, Rollers, and Machinery Protection.

### STORAGE AND HANDLING

**Storage Conditions:** From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

**Note:** The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

### COLOR (S)



Clear

### PRODUCT SPECIFICATIONS

Product Code	Length	Backing Thickness	Total Thickness	Peel Adhesion	Tensile Strength	Elongation	Temperature Resistance
SPT3A	36 YD (33M)	3 mil	5 mil	50 oz/in	20 lb/in	300%	Up to 225 F
SPT5A	36 YD (33M)	5 mil	7 mil	50 oz/in	40 lb/in	350%	Up to 225 F
SPT10A	36 YD (33M)	10 mil	12 mil	50 oz/in	80 lb/in	425%	Up to 225 F
SPT15A	18 YD (16.5M)	15 mil	17 mil	60 oz/in	60 lb/in	300%	Up to 200 F
SPT20A	18 YD (16.5M)	20 mil	22 mil	60 oz/in	60 lb/in	300%	Up to 200 F

- **Note:** Contact Tape Providers for Custom Printed Cores