



SPTA UHMW TAPE

COMPOSITION

Ultra High Molecular Weight Polyethylene with Acrylic Adhesive.

PRODUCT APPLICATIONS

- Reduce Friction, Noise, Wire Harnessing. For Conveyors, Chutes, Rollers, and Machinery Protection.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	18 lbs/in	80.08 N/25 mm
Adhesion to Steel	50 oz/in	13.90 N/25 mm
Thickness	3, 5, 10 Mil	0.07, 0.12, 0.25 mm
Elongation	300% - 350%	- 425%
Temperature Resistance	300 F	149°C

STORAGE AND HANDLING

Storage Conditions: From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

Note: The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

STANDARD LENGTH (S)

- 36 Yards 32.92 Meters
- Contact Tape Providers for other available sizes

COLOR (S)



Clear

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
6	144
Custom Available	



- **Note:** Contact Tape Providers for Custom Printed Cores