

SPTA UHMW TAPE

COMPOSITION

Ultra High Molecular Weight Polyethylene with Acrylic Adhesive.

PRODUCT APPLICATIONS

- Reduce Friction, Noise, Wire Harnessing. For Conveyors, Chutes, Rollers, and Machinery Protection.

STORAGE AND HANDLING

Storage Conditions: From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

Note: The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

COLOR (S)



Clear

PRODUCT SPECIFICATIONS

Product Code	Length	Backing Thickness	Total Thickness	Peel Adhesion	Tensile Strength	Elongation	Temperature Resistance
SPT3A	36 YD (33M)	3 mil	5 mil	50 oz/in	20 lb/in	300%	Up to 225 F
SPT5A	36 YD (33M)	5 mil	7 mil	50 oz/in	40 lb/in	350%	Up to 225 F
SPT10A	36 YD (33M)	10 mil	12 mil	50 oz/in	80 lb/in	425%	Up to 225 F
SPT15A	18 YD (16.5M)	15 mil	17 mil	60 oz/in	60 lb/in	300%	Up to 200 F
SPT20A	18 YD (16.5M)	20 mil	22 mil	60 oz/in	60 lb/in	300%	Up to 200 F

- **Note:** Contact Tape Providers for Custom Cores