

SSLDFT Low Density PVC Foam Tape

COMPOSITION

Low Density Closed Cell PVC Foam Tape with Acrylic Adhesive Coating on One Side and Carried on a White Siliconized Paper Liner.

PRODUCT APPLICATIONS

- Automotive, HVAC, Construction, Window Sealing, Gasketing, Vibration Control, Electronics, and Door Frames.

PHYSICAL PROPERTIES

STANDARD METRIC

Tensile Strength	>15 psi	
Adhesion to SST	>12 oz/in	
Force to Compress (25%)	3.0-4.0 psi	
Compression Deflection	1.2-2.5 psi	
Temperature Resistance	-4 °F to 176 °F	-15 °C to 80 °C

STORAGE AND HANDLING

Storage Conditions: Cool and dry area. No direct sun.

COLOR (S)



Black



Gray





TABLE OF MEASUREMENTS

Width	Thick IN	Thick MM	Length
1/16" (0.063")	3/16	4.7	150 FT
	1/4	6	
	3/8	9	
	1/2	12	
	5/8	15	
	3/4	18	
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	56	1372	

Width	Thick IN	Thick MM	Length
1/8" (0.125")	3/16	4.7	75 FT
	1/4	6	
	3/8	9	
	1/2	12	
	5/8	15	
	3/4	18	
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	58	1372	

Width	Thick IN	Thick MM	Length
3/16" (0.188")	1/4	6	50 FT
	3/8	9	
	1/2	12	
	5/8	15	
	3/4	18	
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	58	1372	

Width	Thick IN	Thick MM	Length
1/4" (0.25")	1/4	6	35 FT
	3/8	9	
	1/2	12	
	5/8	15	
	3/4	18	
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	58	1372	

Width	Thick IN	Thick MM	Length
3/8" (0.375")	3/8	9	30 FT
	1/2	12	
	5/8	15	
	3/4	18	
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	5	1372	

Width	Thick IN	Thick MM	Length
1/2" (0.5")	1/2	12	25 FT
	5/8	15	
	3/4	18	
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	58	1372	

Width	Thick IN	Thick MM	Length
3/4" (0.75")	3/4	18	15 FT
	7/8	21	
	1	24	
	1.5	36	
	2	48	
	58	1372	