



## UFST39 UNI-DIRECTIONAL FILAMENT TAPE

### COMPOSITION

Mono Directional Fiber Glass Synthetic Rubber Adhesive Reinforced with BOPP Film

### PRODUCT APPLICATIONS

- Bundling, Carton Sealing, Strapping, and Shipping.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	112 lbs/in	500 N/25 mm
Adhesion to Steel	72 oz/in	20 N/25 mm
Thickness	3.5 mils	0.090 mm
Elongation	6%	6%
Temperature Resistance	140 F	60°C

### STORAGE AND HANDLING

**Storage Conditions:** From 15°C/59°F to 25°C/77°F with max. relative humidity of 65%.

**Note:** The material should be stored away from heat sources and possibly kept in the original package, avoiding light exposure as well.

### STANDARD LENGTH (S)

- 60 Yards 55 Meters
- Contact Tape Providers for other available sizes

### COLOR (S)



Clear

### TABLE OF MEASUREMENTS

#### STANDARD WIDTH(S)

IN	MM
3/8	9
1/2	12
3/4	18
1	24
1.5	36
2	48
3	72
4	96
6	144
Custom Available	



- **Note:** Contact Tape Providers for Custom Printed Cores