

VDTY4

DRY VINYL TAPE

NON-ADHESIVE



COMPOSITION

Non-adhesive plasticized polyvinyl chloride film tape

PRODUCT APPLICATIONS

- Used for plating applications - high stretch, good “cling” characteristics and great conformability provide for superior masking in hard chrome and other plating applications.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	8.6 lbs/in	38.09 N/10 mm
Thickness	3.94 mils	0.10 mm
Elongation	200%	200%
Meets Certificate Standard	CE	
UL510 Flame Resistant		

STORAGE AND HANDLING

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

STANDARD LENGTH (S)

- 76 Meters
- 250 Feet
- Contact Tape Providers for other available sizes

COLOR (S)

Yellow.

TABLE OF MEASUREMENTS

STANDARD WIDTH(S)

IN	MM
1/2	12
3/4	72
1	25
1.5	36
2	48
3	72
4	96
48	1,220
Custom Available	



- **Note:** Contact Tape Providers for Custom Printed Cores